

Mercedes Benz Actros 5050 K 8X4

Model:	Mercedes-Benz Actros	
Vehicle type:	5050 K	
Drivetrain:	10x4	
Baumuster:	93231512	
Vehicle type:	Tipper chassis	
Driver cabin:	M-Cab with low roof	
Engine power:	370 kW (503 hp)	
Wheelbase:	5600 mm (4500 + 1100)	
Gross vehicle weight: 50000 kg		
Steering type:	left	

Equipmentlist

Paint

cabin:	MB 9147 a	arctic white		
Chassis version				
KCVK Extension of wheelbase by 11	.00 mm (4	4500 + 1100 = 5600)		
Axle load distribution				
KTNC Weight variant 50.0 t (9.0/9.0	0/13.0/13.0	0/ 9.5)		
Engine				
MV6 Engine, V8, LA, 370 kW (503 h	hp), 1800 r	rpm		
MS3 Engine version, Euro III				
M49 Tandem air cleaner system				
K81 Fuel pre-filter, heated water sep	arator			
ML3 High-speed fan, with belt drive				
>>> Engine brake with constantly of	pen throttle	e valve		
>>> Single-cylinder air compressor,	non-regul	ated		
N53 Engine PTO, rear, for hydraulic	pump			
M72 Protective plate under radiator a	and engine	•		
M78 Engine number, stamped-in				
MA9 Engine mountings, for off-road use				

N55 Transmission oil cooling			
NG8 PTO flange, with cross serrations, D=120 mm			
GS3 Gearshift, hydraulic			
N56 PTO, live, MB, 1.4			
N90 Deletion, tipper drive			
NK7 Gearshift interlock, live PTO (NMV)			
Axles & suspension			
A91 Front axle, straight version			
>>> Front axle load compensating system AL5 Front axle 9.0 t			
AM3 Rear axle H7, 13.0 t, crown wheel 300 >>> Differential lock rear axle			
AR1 Axle ratio i = 5.333 (HL7)			
QD1 Front spring, 9.0 t,			
QF3 Rear spring, 15.0 t, hard			
>>> Stabilizer front axle			
C42 Stabiliser, rear axle, under frame			
C 12 Submiser, rear axie, under mane			
Wheels & tyres			
RA9 Tapered rims, 11.75x22.5 on front axle			
R38 Tapered rims, 9.00 x 22.5			
R04 Wheel nut cap			
1.A. W48K16 10 2x 385/65 R 22.5 Highway "K"			
2.A. W48K16 10 2x 385/65 R 22.5 Highway "K"			
3.A. F18L76 13 4x 315/80 R 22.5 TL Traction (M+S) "L"			
4.A. F18L76 13 4x 315/80 R 22.5 TL Traction (M+S) "L"			
Frame and components attached to frame			
CL9 Steering LS 6/LS 8			
>>> Implement carrier, left			
KU2 Main tank, 300 l, aluminium			
K40 Tank-cap lock			
K45 Screen, tank filler neck K68 Exhaust silencer(s), vertical, behind cab			
P44 Wing, for chassis transit			
C63 Bumper, steel version			
C95 Deletion, rear underride guard (EC)			
Q18 End crossmember, bolted			
Q10 Elia crossincinoci, conca			
Brake system			
>>> Dual-circuit full air brakes			
>>> Automatic brake adjusting			
>>> Roll back prevention			
BB6 Drum brakes on front and rear axle			
BB0 Anti-lock braking system (ABS), disengageable			
BB8 Telligent braking system with ABS and ASR			
B65 Compressed air dryer, heated			

F05	M-cab
DD1	Cab with low roof, standing room 1400 mm
F24	Cab rear wall, straight
F35	Cab rear wall with window
FL6	Cab mountings, standard
FC7	Windows, tinted, without sun filter
D25	Roof hatch/vent, roof
FE6	Cab steps, movable
FS2	Wide-angle mirror on driver's side, heated
FT0	Exterior rear-view mirror, grooved cover
>>>	Wide-angle exterior mirror on front passenger side
	Electrical adjustable, heated rearview mirrors
	Ramp mirror on co-driver's side
	Immobiliser, with transponder
	Central locking system
Cab inter	rior
	Driver's comfort suspension seat, Grammer
	Fold-up seat, velour, co-driver
>>>	Steering column-rake and height adj. w. pneum lock
>>>	multi-function steering wheel
FN1	Distribution cockpit
FE5	Power windows for driver's/co-driver's door
JK2	Instrument cluster, graphics-capable display
	Tachograph, 1 day + 2 drivers, modular
>>>	Outside temperature gauge
>>>	Fuel consumption display
	Reversing warning device
	Telligent Maintenance System
	Provision, 12-V radio, retrofit
	Voltage transformer, 24 V/12 V, 15 A
	Construction-site filter
>>>	Air controlled heating/ventilation system
	Air conditioning system
Electrics	/ electronics
M45	Alternator 28 V/100 A
EM8	PSM, body and trailer CAN, ISO 11992
>>>	Headlamp range adjuster
>>>	Headlamp unit, H7, with clear-lens look
	6-part tail light cluster with reflector
	Indicator transmitter for extra indicator lamps
	Speed limiter, electronic, 85 km/h
	Cruise control
-	
Addition	al scopes
	Deletion, noise reduction measures
Y10	First aid kit
Y44	Hazard warning triangle
	Warning lamp

Y20 Tools for export	
Y34 Tyre inflating hose, 10 m	
YK4 Compressed-air gun, supplied loose	
Y28 2 wheel chocks	
XK3 Powertrain warranty, Gen. Terms/Con., 3 yrs/250000 km	
XV6 Actros 3	
X38 Model identification, acc. to weight variant	
X49 Labels/publications, netherlands	
ZZ3 Vehicle, for right-side traffic	
>>> including all necessary modifications	