

Mercedes Benz Actros 5050 K 8X4

Model:	Mercedes-Benz Actros	
Vehicle type:	5050 K	
Drivetrain:	10x4	
Baumuster:	93231512	
Vehicle type:	Tipper chassis	
Driver cabin:	M-Cab with low roof	
Engine power:	370 kW (503 hp)	
Wheelbase:	5600 mm (4500 + 1100)	
Gross vehicle weight: 50000 kg		
Steering type:	left	

Equipmentlist

Paint

cabin:

MB 9147 arctic white

Chassis version

KCVK Extension of wheelbase by 1100 mm (4500 + 1100 = 5600)

Axle load distribution

KTNC Weight variant 50.0 t (9.0/9.0/13.0/13.0/ 9.5)

Engine

MV6 Engine, V8, LA, 370 kW (503 hp), 1800 rpm
MS3 Engine version, Euro III
M49 Tandem air cleaner system
K81 Fuel pre-filter, heated water separator
ML3 High-speed fan, with belt drive
>>> Engine brake with constantly open throttle valve
>>> Single-cylinder air compressor, non-regulated
N53 Engine PTO, rear, for hydraulic pump
M72 Protective plate under radiator and engine
M78 Engine number, stamped-in
MA9 Engine mountings, for off-road use

Clutch & transmission

GC2 Transmission G 240-16/11.7-0.69

N55	Transmission oil cooling
NG8	PTO flange, with cross serrations, D=120 mm
GS3	Gearshift, hydraulic
N56	PTO, live, MB, 1.4
N90	Deletion, tipper drive
NK7	Gearshift interlock, live PTO (NMV)

Axles & suspension

- A91 Front axle, straight version
- >>> Front axle load compensating system
- AL5 Front axle 9.0 t
- AM3 Rear axle H7, 13.0 t, crown wheel 300
- >>> Differential lock rear axle
- AR1 Axle ratio i = 5.333 (HL7)
- QD1 Front spring, 9.0 t,
- QF3 Rear spring, 15.0 t, hard
- >>> Stabilizer front axle
- C42 Stabiliser, rear axle, under frame

Wheels & tyres

RA9 Tapered rims, 11.75x22.5 on front axle
R38 Tapered rims, 9.00 x 22.5
R04 Wheel nut cap
1.A. W48K16 10 2x 385/65 R 22.5 Highway "K"
2.A. W48K16 10 2x 385/65 R 22.5 Highway "K"
3.A. F18L76 13 4x 315/80 R 22.5 TL Traction (M+S) "L"
4.A. F18L76 13 4x 315/80 R 22.5 TL Traction (M+S) "L"

Frame and components attached to frame

- CL9 Steering LS 6/LS 8
- >>> Implement carrier, left
- KU2 Main tank, 300 l, aluminium
- K40 Tank-cap lock
- K45 Screen, tank filler neck
- K68 Exhaust silencer(s), vertical, behind cab
- P44 Wing, for chassis transit
- C63 Bumper, steel version
- C95 Deletion, rear underride guard (EC)
- Q18 End crossmember, bolted

Brake system

Drane of		
>>>	Dual-circuit full air brakes	
>>>	Automatic brake adjusting	
>>>	Roll back prevention	
BB6	Drum brakes on front and rear axle	
BB0	Anti-lock braking system (ABS), disengageable	
BB8	Telligent braking system with ABS and ASR	
B65	Compressed air dryer, heated	

F05	M-cab
DD1	Cab with low roof, standing room 1400 mm
F24	Cab rear wall, straight
F35	Cab rear wall with window
FL6	Cab mountings, standard
FC7	Windows, tinted, without sun filter
D25	Roof hatch/vent, roof
FE6	Cab steps, movable
FS2	Wide-angle mirror on driver's side, heated
FT0	Exterior rear-view mirror, grooved cover
>>>	Wide-angle exterior mirror on front passenger side
>>>	Electrical adjustable, heated rearview mirrors
>>>	Ramp mirror on co-driver's side
FZ7	Immobiliser, with transponder
>>>	Central locking system
Cab inter	
	Driver's comfort suspension seat, Grammer
	Fold-up seat, velour, co-driver
	Steering column-rake and height adj. w. pneum lock
	multi-function steering wheel
	Distribution cockpit
	Power windows for driver's/co-driver's door
	Instrument cluster, graphics-capable display
	Tachograph, 1 day + 2 drivers, modular
	Outside temperature gauge
	Fuel consumption display
	Reversing warning device
	Telligent Maintenance System
	Provision, 12-V radio, retrofit
	Voltage transformer, 24 V/12 V, 15 A
HF1	Construction-site filter
>>>	Air controlled heating/ventilation system
H03	Air conditioning system
	/ electronics
M45	Alternator 28 V/100 A

- EM8 PSM, body and trailer CAN, ISO 11992
- >>> Headlamp range adjuster
- >>> Headlamp unit, H7, with clear-lens look
- >>> 6-part tail light cluster with reflector
- >>> Indicator transmitter for extra indicator lamps
- MK6 Speed limiter, electronic, 85 km/h
- MD9 Cruise control

Additional scopes

- XW9 Deletion, noise reduction measures
- Y10 First aid kit
- Y44 Hazard warning triangle
 - Y45 Warning lamp

Y20 Tools for export
Y34 Tyre inflating hose, 10 m
YK4 Compressed-air gun, supplied loose
Y28 2 wheel chocks
XK3 Powertrain warranty, Gen. Terms/Con., 3 yrs/250000 km
XV6 Actros 3
X38 Model identification, acc. to weight variant
X49 Labels/publications, netherlands
ZZ3 Vehicle, for right-side traffic
>>> including all necessary modifications