

Mercedes-Benz Actros 4031-K 6x4

A91	Front axle, straight
AL5	Front axle
AM6	Rear axle H7 16,0t with crown wheel 300
AQ8	Axle ratio 1 = 5,143 (HL7)
BB0	ABS with deactivation facility
BB6	Drum brakes on front axle and rear axle
BB8	Telligent-brake system with abs and asr
C63	Bumper, steel version
C95	Deletion of EC under-ride guard rear
CL9	LS 6/ LS 8 Steering
CR4	Fasteningparts on frame or hole grid
D25	Roof hatch/roof fan
E39	Automatic fuses
E84	Battery box lockable
E86	Batterie-Sensor
EU1	CD-Radio
F07	Cab s (standard = short)
F24	Cab with straight rear wall
F34	Cab rear wall without window
F52	sun visor outside transparent
FE5	Electr. Window lifts driver and front pass.door
FE6	Access steps left and right, movable
FL3	Reinforced spring strut bearing
FL6	Cab suspension for rough terrain (6 HZ)
FM2	All Round tintedglaz, windsh.w green sun filt
FN1	Straight instrument panel support, short, hard
FS2	Heated mirror at front seat
FW2	Deletion of immobilizier (transponder)
FZ9	Two master keys / transmitters extra
G81	Clutch reinforced
GC3	Gearbox G 210-16 / 14,2-0,83
GS7	Telligent gearshift system 2
GZ6	Gearbox supplier valeo
H03	Air conditioning system
HF1	Construction site filter
IL2	Export Code
IL8	Left handsite
IQ5	Wheel position 3900mm
IV7	33,0 tons
IX6	V-engine – 6 cylinder
J10	Tachometer km
J70	Compressed-air horn
JK2	Instrument cluster with graphics-caable display
JM1	Speedometer Km
JW0	Reversing warner
K40	Tank filler cap lockable
K45	Fuel filter screen in filler neck
K81	Primary fuel filter with heated water separator
KH7	Silencer with tail pipe at side
KH9	Exhaust system positioned further back

GMC.EU

KI0	Protection, underneath main tank
KS4	Main tank 400 liters, steel
L30	Protective grille for headlamps
L54	Revolving flasher yellow left + right on cab roof
L72	Electric system for non-DB Body
LH4	Rearlight blue, steel with cage
M49	tandem air cleaner system
M72	Protector, underneath cooler and engine
M78	Engine number embossed
MA9	Engine mounts for rough road operation
MD9	Cruise control
MP0	Engine packagr for heavy operations
MP2	Cooling system reinforced
MS0	Engine version, euro II
MT7	Speed limiter 80km/h elec
MX1	Engine, V6, LA, 230kW (313PS) 1800/min
N55	Gear Oil cooler
NH1	Countershaft PTO ZF, 2B 1,44
P44	Mudguards für transfer of chassis
Q18	End cross member bolted
QD9	Front springs 9,0 t , assymmetric
QF9	Rear springs 18,0 t, 1450mm
R04	Wheel nut cover
R28	Advanced rims 8,5-24 for 12.00-24
R60	Provisional spare wheel mounting
R87	Dropcenter rims fa 22.5 x 9.00
SF0	Folding seat on co driver side w seat belt
XV6	Actros 3
XW9	Deletion of noise measures
Y10	First aid kit
Y27	1 wheel chock placed in cab, loose
Y34	Tire inflating hose 25m
Y44	Warning triangle
Y45	Warning lampe
Y74	Jack, 25t
Z01	Execution according country
ZZ3	Right hand drive