

Mercedes-Benz 3332 B 6x4 3300 with SANY 8 cbm. mixer

Colour

LA1 9147 arctic white

Axle load distribution

TT6 Weight variant 33.0 t (7.5/13.0/13.0)

Engine

MV1 Engine, V6, LA, 235 kW (320 hp), 1800 rpm
MS3 Engine version, Euro 3
MG8 Top air intake rear, frame-mounted air cleaner
M60 Paper air cleaner , larger
M67 Cyclone pre-filter
K81 Fuel pre-filter, heated water separator
MP2 Engine cooling power increased
N52 Engine takeoff, rear, torque 600 Nm
N54 Coupling, flexible, for engine takeoff (loose)
MA9 Engine mountings, for off-road use

Clutch & transmission

G81 Clutch, reinforced
GC3 Transmission G 210-16/14.2-0.83
N55 transmission oil cooling
GS3 Gearshift, hydraulic

Axles & suspension

A91	Front axle, straight version
AL3	Front axle 7.5 t
AM3	Rear axle H7, 13.0 t, crown wheel 300
AP6	Axle ratio $i = 4.143$ (HL7)
QY1	Front spring, 9.0 t, hard
QF6	Rear spring, 16.0 t, hard
CD4	Stabiliser reinforced, 2nd rear axle

Wheels & tyres

A1 F18K29 10 x2	315/80 R 22,5 highway
A2 F18K29 10 x4	315/80 R 22,5 TL Traction (S+G)
A3 F18K29 10 x4	315/80 R 22,5 TL Traction (S+G)
R38	Tapered rims, 9.00x22.5
R04	Wheel nut cap

Frame and components attached to frame

CR4	Mounting parts on frame/hole pattern
CL9	Steering LS 6/LS 8
KS2	Main tank, 300 l, steel
K40	Tank-cap lock
K68	Exhaust silencer(s), vertical, behind cab
K45	Screen, tank filler neck
K68	Exhaust silencer(s), vertical, behind cab
P44	Mudguard, for chassis transit
C63	Bumper, steel version
Q29	Trailer/tow-away coupling, Ringfeder
Q57	Tow-away coupling, rear

Brake system

BB5	Disc brakes on front and rear axle
BB0	Anti-lock braking system (ABS), disengageable
BB8	Telligent braking system with ABS and ASR
B65	Compressed air dryer, heated

Cab exterior

F07	S-cab
F24	Cab rear wall, straight
F35	Cab rear wall with window
FL3	Cab mountings, rear reinforced
FL6	Cab mountings standard
FC7	Windows, tinted, without sun filter
D25	Roof hatch/vent, roof
FE6	Cab steps, movable
FT0	Exterior rear-view mirror, grooved cover
F94	Deletion, front mirror
F52	Sun visor, exterior, transparent

Cab interior

SG5	Driver's standard suspension seat, Isringhausen
SF0	Fold-up seat, co-driver
ES8	Additional socket, 24 V / 15 A, firewall
FN1	Distribution cockpit
FE5	Power windows for driver's/co-driver's door
JK2	Instrument cluster, graphics-capable display
J10	Tachometer km
JW0	reversing warning device

EV6	Provision, 12-V radio, retrofit
EV2	Provision for fitting CB radio
EV5	Provision for fitting telephone, fax
ET1	Voltage transformer, 24 V/12 V, 8 A
HF1	Construction-site filter
H03	Air conditioning system

Electrics / electronics

EB3	Batteries, 2 x 12 V / 220Ah, low - maintainance
E84	Battery box, lockable
L72	Elektrics, for non-MB body
EM8	PSM, body and trailer CAN, ISO 11992
EM9	PSM, body CAN, ISO 11898 instead of 11992
MD4	Speed limiter, 90 km/h, EC
MD9	Cruise control

Additional scopes

X57	Noise reduction measures, EC 96/20
Y10	First aid kit
Y16	Fire extinguisher
Y44	Hazard warning triangle
Y45	Warning lamp
YK4	Compressed-air gun, supplied loose
Y34	Tyre inflating hose, 25 m
Y28	2 wheel chocks
Y74	Jack, 25 t
XK3	Powertrain warranty, Gen. Terms/Con., 3 yrs/250000 km
XV6	Actros 3
X38	Model identification, acc. to weight variant
ZZ3	Vehicle, for right-side traffic