

pk trucks holland

Showroom: Graanweg 2 (M200) 4782 PP Moerdijk The Netherlands Tel. : +31 168 382 032 Fax : +31 168 382 023 E-mail: pktrucks@pktrucks.com

Schwing concrete pump S 36 X

Placing boom 36 R

Compact 4-section placing boom in roll and fold design, made of fine grain steel with attached pipeline, resting on a slewable base column with fully hydraulic and telescopic outriggers. Operation of the boom by proportional electric remote control. Manual controls for recovery.

Technical Data

| Number of articulations Vertical reach | 4 35,30 m |
|---|--------------|
| Horizontal reach from | |
| centre of slewing axis | 31,30 m |
| Slewing range | 2 x 370° |
| 0 | , |

<u>Pump kit</u>

Fitted with the SCHWING Rock Valve with automatic adjustment of the cutting ring by means of a prestressed rubber spring. Easy access for cleaning and maintenance resulting in low wearing costs.

Ready-to-operate concrete pump. Fully hydraulic concrete pump control system in the reliable open hydraulic circuit. Easy to operate and to maintain. Prime coated and finished .

Technical Data

Type hydr. drive V (max) theor. concrete output diam. of pumping cylinders piston stroke max. number of strokes capacity of agitator hopper approx. charging height approx. drive system rock valve system pumping cylinder execution electr. vibrator cover for hopper P 2023-110/75 636 L / min. 164 m³ / h 230 mm 2.000 mm 33 / min 400 L 1.350 mm two circuit hydraulic M-rock DN 230 chrome-plated on hopper grate with, including locking

www.pktrucks.com



pk trucks holland

Showroom: Graanweg 2 (M200) 4782 PP Moerdijk The Netherlands

standard

4 m DN 125

Tel.: +31 168 382 032 Fax: +31 168 382 023 E-mail: pktrucks@pktrucks.com

<u>Pipeline</u> boom pipeline pipeline outlet to boom outlet variants end hose

Base frame outrigger system outrigger pads

full-support PE - pads

Super 2000 DN 125

Super 2000 DN 125

Operation system control system

VECTOR

The microcontroller-based control system VECTOR used to convert the machine function in the mode local, remote and ramp change. The system offers next to an integrated diagnostic system a wide range of assistance to help and relieve the machine operator in the operation and maintenance of the concrete pump.

language Control system remote control

english Schwing control 30

Proportional remote control Schwing control 30 with 2 joysticks and display for metering general machine parameter. The SCHWING Control 30 can be used in wireless and cable linked mode.

Scope of supply: 1 x transmitter with carrying strap, 1 x receiver, 2 x rechargeable batteries, 1 x battery recharger, 1 x 20 m cable for teach- and cable linked mode.

additional transmitter horn tracer hopper area concrete output adjustment 1 x on the right side with, 0 - max.

Lighting

spot hopper area

Delivery System

water tank Water system water tank filling cover water tank hydraulic oil filling oil cooler execution central creasing system supply control at the hopper left

420 L, front left side Roller water pump c-connection serial with hydraulic oil HVLP 46 electrically driven cooler fan central greaser strip Rock with

www.pktrucks.com



pk trucks holland

Showroom: Graanweg 2 (M200) 4782 PP Moerdijk The Netherlands Tel. : +31 168 382 032 Fax : +31 168 382 023 E-mail: pktrucks@pktrucks.com

The new supply control and integrated local control at the rear of a SCHWING truck mounted concrete pump enables the machinist to control all functions and operations for the work preparation, cleaning and maintenance of his machine, without climbing onto the machine. Furthermore, the hydraulic pressure of the concrete pump and MPS can be read.

Painting

Scope of paint color code color of cabin labeling

Documents

language labeling language operating manual language spare part list number of spare part list painted in one color MB 9147 arctic white MB 9147 arctic white SCHWING standard

english english (2x) english 1 (+

www.pktrucks.com