



pk trucks holland

Showroom: Graanweg 2 (M200)
4782 PP Moerdijk
The Netherlands

Tel. : +31 168 382 032
Fax : +31 168 382 023
E-mail: pktrucks@pktrucks.com

Mercedes Benz Unimog off road U4000 4x4 – NEW

Colour

LA1 MB 9678 pure white

Vehicle specifications

VB6 Euro 3 off road
Z01 Left hand drive vehicles
X21 Increased weight variant

Suggested delivery

>>> 3 - point automatic seat belts
S50 First aid kit

Engine

MQ4 MB 4-Cylinder Diesel Engine OM924LA, 160kW (218PS)
M88 Soundproofing (to 70/157/EG and 96/20/EG)
MS3 Euro 3
>>> PLD - engine injection (pump/line/nozzle)
>>> Turbocharging and intercooling
>>> 2-stage engine brake (constantly open throttle/throttle valve)
>>> Motor control characteristics, switch, driver/devices
>>> Manual throttle, electronic
>>> Air compressor, 310l/min 18bar, maintenance-free, water-cooled
>>> Air intake with air filter and separation
M61 Water separator in the fuel system
N18 Preparation for gearbox PTO
>>> Fan drive, (KR), viscous coupling, water-cooled mechanical
>>> Maintenance interval, 1200 Hour/30.000 km
>>> Immobilizer (clutch control)

Gearbox

G22 Transmission with off road group
>>> Single-plate dry clutch, self-adjusting
>>> Electro-pneumatic circuit (EPS)
>>> MB full-synchronised reversing transmission with 8 forward and 6 reverse gears

www.pktrucks.com



pk trucks holland

Showroom: Graanweg 2 (M200)
4782 PP Moerdijk
The Netherlands

Tel. : +31 168 382 032
Fax : +31 168 382 023
E-mail: pktrucks@pktrucks.com

- >>> Front-wheel drive, pneumatically activated (all-wheel)
- >>> Cruise control/speed limiter
- >>> Electro-pneumatic reversing function (EQR)

Axles

- >>> Front axle as stepped axle/portal axle
- >>> Differential lock on front axle
- >>> Rear axle as a stepped axle
- >>> Differential lock on the rear axle
- >>> Axle ratio $i = 6.53$
- >>> Power steering, hydraulic
- >>> Coil springs with progressive characteristic line

Tyres

- R60 365/85 R 20 single wheel mounted
- 1.A. 984K56 80 2 x 365/80 R 20 Terrain Michelin XZL
- 2.A. 984K56 80 2 x 365/80 R 20 Terrain Michelin XZL

Chassis and components attached to chassis

- >>> Flexible, ladder-type frame with high torsional flexibility
- >>> 3-point mountings for engine, transmission
- >>> Tank 145 l, left, steel
- >>> Tanks, lockable
- >>> Exhaust system, exhaust down
- >>> Front towing jaw with pin
- >>> Anti-corrosion underbody protection (Dinol)

Brake system

- >>> Pneumatic/hydraulic high-pressure braking system (18 bar)
- >>> Automatic load-sensitive brake pressure control (ALB)
- >>> Disc brakes (FA and RA)
- >>> Anti-lock braking system (ABS), can be deactivated off road
- >>> Compressed Air Dryers
- >>> Compressed air connection for auxiliary loads
- >>> Tyre inflation connection
- >>> Spring-loaded parking brake

www.pktrucks.com



pk trucks holland

Showroom: Graanweg 2 (M200)
4782 PP Moerdijk
The Netherlands

Tel. : +31 168 382 032
Fax : +31 168 382 023
E-mail: pktrucks@pktrucks.com

Cab exterior

- >>> Cab, all-steel design
- >>> Cab strength according to ECE - R - 29/2
- F07 Cab extended (double cabin)
- >>> Roof ventilation flap, rectangular
- >>> Hood, elevatably, removable
- F64 Cab components for body
- >>> Cab, tiltable
- >>> FHS storage, 3-point anti-vibration
- >>> Windscreen, laminated glass, thermal insulation
- >>> Wiper system, 3 stepped, intermittent wipers
- >>> Rear wall window, fixed, on both sides
- >>> Door window
- >>> Main mirror, heated, electrically adjustable
- S82 Wide-angle mirror
- S83 Ramp mirror

Cab interior

- >>> Cabin floor, with hatch option
- >>> Steering column switch, right (driving)
- >>> Steering column switch, left (high beam, windscreen wipers)
- >>> Driver's seat height, length, angle adjustable, cloth
- S12 Passenger seat two-seater
- >>> Fahrerinformation the System (FIS)
- >>> On board Diagnose
- >>> Continuous current socket 24V/15A, in center console
- >>> Heating Ventilation system, fan, dust filter
- F57 Air conditioning company Süttrac
- >>> Cubbyholes and storage box
- >>> Overhead control panel (Radio/Tachograf)
- >>> Door trim, with armrest and bottle holders

Electronics

- >>> Batteries 2 x 12V/66Ah
- >>> Generator 28V/100A
- >>> Trailer socket 24V, 15-pin
- L35 Headlight leveling system

www.pktrucks.com



pk trucks holland

Showroom: Graanweg 2 (M200)
4782 PP Moerdijk
The Netherlands

Tel. : +31 168 382 032
Fax : +31 168 382 023
E-mail: pktrucks@pktrucks.com

- >>> Tail, reversing lights, fog, and clearance light
- L71 Side marker lights with integrated reflector
- L30 Fogs for headlights
- >>> Speed limiter, 90 km/h ECE
- >>> Electrical board network 24V
- >>> Electrical, EMC tested

Building

P61 Underbody for special bodies

Additional scopes

- >>> Fordability 800 mm
- Y31 Tire inflation hose with pressure gauge
- >>> Jacks hydraulic
- >>> Hand tools
- >>> Wheel chocks, 2-fold
- W60 German as a language
- X38 Lubrication schedule English

Technical data

Weight without building

1. Front axle (empty)	3598 kg.
1. Rear axle (empty)	1577 kg.
Empty total (incl. SA)	5175 kg.
Payload	4325 kg.
Maximum weight allowed	9500 kg.
Permissible total weight truck	0 kg.

Engine

	<i>MQ4</i>
Displacement cm ³	4801
Power kW / hp	160/218
Max . Torque in NM at 1600/min	810

Transmission

Short text: MB, fully synchromesh gearbox, UG100, 8 forward and 6 reverse gears.

www.pktrucks.com